

RZR

POLARIS
OFF-ROAD VEHICLES



RZR DYNAMIX™ calculates 7-vehicle inputs over 200-times per-second to deliver the best ride at any moment:

- » Vehicle Speed
- » Brake Pedal Position
- » Throttle Pedal
- » Mode Switch
- » Steering Wheel Position
- » Accelerometer
- » Gyroscope

INTRODUCING THE ALL-NEW

RZR XP® TURBO S

DYNAMIX
ACTIVE SUSPENSION

**FUEL YOUR
PASSION**

THE FUTURE OF RIDE AND HANDLING IS HERE

Introducing RZR DYNAMIX™ Active Suspension. The world's first and only intelligent suspension system designed for the off-road. RZR DYNAMIX™ electronically controls and adjusts shock damping to deliver the best ride in any terrain.

ADJUSTS 200 TIMES-PER-SECOND

RZR® 2018 SPECIFICATIONS



x2



x2



x2 / x4



x2 / x4

	RZR 900	RZR S 900 EPS	RZR XP TURBO EPS / *RZR XP 4 TURBO EPS	RZR XP TURBO DYNAMIX / *RZR XP 4 TURBO DYNAMIX
ENGINE TYPE	ProStar 900 4-Stroke DOHC Twin-Cylinder	ProStar 900 4-Stroke DOHC Twin-Cylinder	ProStar Turbo H.O 4-Stroke DOHC Twin-Cylinder Turbocharged	ProStar Turbo H.O 4-Stroke DOHC Twin-Cylinder Turbocharged
HORSEPOWER	75 HP	75 HP	168 HP	168 HP
DRIVE SYSTEM	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD
ENGINE BRAKING SYSTEM	Standard	Standard	Not Equipped	Not Equipped
FRONT SUSPENSION	Dual A-Arm with Stabilizer Bar and 254 mm Travel	Dual A-Arm with 311 mm Travel	Dual A-Arm with Stabilizer Bar 406 mm Travel	Dual A-Arm with Stabilizer Bar and 406 mm Travel
FRONT SHOCKS	ZF Sachs	2" Walker Evans Needle	FOX 2.5 PODIUM LSC Internal Bypass	FOX 2.5 PODIUM Live Valve with Bottom-Out Control
REAR SUSPENSION	Dual A-Arm with Stabilizer Bar with 254 mm Travel	Dual A-Arm with Stabilizer Bar with 335 mm Travel	Trailer Arm with Stabilizer Bar with 457 mm Travel	Trailing Arm with Stabilizer Bar with 457 mm Travel
REAR SHOCKS	ZF Sachs	2" Walker Evans Needle	FOX 2.5 PODIUM LSC Internal Bypass	FOX 2.5 PODIUM Live Valve with Bottom-Out Control
FRONT TYRES	26 x 8-12	27 x 9-12	29 x 9-14	29 x 9-14
REAR TYRES	26 x 9-12	27 x 11-12	29 x 11-14	29 x 11-14
WHEELS	Stamped Steel	Cast Aluminium	Cast Aluminium	Cast Aluminium
WHEELBASE	2007 mm	2007 mm	2286 mm / *2972 mm	2286 mm / *2972 mm
DRY WEIGHT	522 kg	558 kg	671 kg / 758 kg	671 kg / *769 kg
OVERALL SIZE (L X W X H)	2667 x 1270 x 1765 mm	2692 x 1524 x 1816 mm	3022 x 1626 x 1873 mm *3708 x 1626 x 1873 mm	3022 x 1626 x 1873 mm *3708 x 1626 x 1873 mm
GROUND CLEARANCE	279 mm	318 mm	343 mm	343 mm
FUEL CAPACITY	36 L	36 L	36 L	36 L
BED BOX DIMENSIONS	525 x 940 x 200 mm	525 x 940 x 200 mm	720 x 570 x 178 mm	720 x 570 x 178 mm
REAR RACK CAPACITY	136 kg	136 kg	136 kg	136 kg
PAYLOAD CAPACITY	336 kg	336 kg	336 kg / *408 kg	336 kg / *408 kg
LIGHTING	Halogen, 55W Low 60W High & Red LED Tail / Brake Lights	Halogen, 55W Low 60W High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights RIDE COMMAND 7" Control System Rear Wired Camera

For more information and specifications visit

www.polarissa.co.za

POLARIS SOUTH AFRICA SUPPORTS RESPONSIBLE RIDING. FOR YOUR SAFETY, ALWAYS WEAR A HELMET, EYE PROTECTION, PROTECTIVE CLOTHING AND NEVER CARRY PASSENGERS UNLESS THE ATV OR SIDE X SIDE HAS BEEN DESIGNED BY THE MANUFACTURER SPECIFICALLY FOR THAT PURPOSE. MODELS ARE FOR RIDERS AGED 16 YEARS AND OLDER. CONTACT YOUR DEALER FOR COLOUR OPTIONS. E60E