

RANGER

Delivering on our hardest working, smoothest riding promise, *RANGER* offers the most powerful lineup, the best handling and the largest breadth of integrated accessories. You can do more, tow more, haul more and ride more.

**GET MORE
DONE**



RANGER 2018 SPECIFICATIONS



2



2



X3 / X6



X3 / X6



X3 / X6



X3

ALL-NEW

	RANGER EV	RANGER 500	RANGER 570 FULL-SIZE *AVAILABLE IN CREW	RANGER XP 900 *AVAILABLE IN CREW	RANGER DIESEL *AVAILABLE IN CREW	RANGER XP 1000 EPS
ENGINE TYPE	Single 48-Volt, High Efficiency AC-Induction Motor	ProStar 500cc, 4-Stroke Single-Cylinder	ProStar 567cc 4-Stroke Single-Cylinder DOHC	ProStar 875cc, 4-Stroke Twin-Cylinder DOHC	Kohler 1028cc, 3-Cylinder Diesel	ProStar 999cc 4-Stroke Twin-Cylinder DOHC
HORSEPOWER	30 HP	32 HP	44 HP	68 HP	24 HP	82 HP
DRIVE SYSTEM	On-Demand True AWD / 2WD VersaTrac Turf Mode	On-Demand True AWD / 2WD VersaTrac Turf Mode	On-Demand True AWD / 2WD VersaTrac Turf Mode	On-Demand True AWD / 2WD VersaTrac Turf Mode	On-Demand True AWD / 2WD VersaTrac Turf Mode	High Perf, On-Demand True AWD / 2WD VersaTrac Turf Mode
ENGINE BRAKING SYSTEM / ACTIVE DESCENT CONTROL	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Standard
FRONT SUSPENSION	MacPherson Strut 229 mm Travel	MacPherson Strut 229 mm Travel	MacPherson Strut 229 mm Travel	Dual A-Arm 254 mm Travel	Dual A-Arm, 254 mm Travel	Dual A-Arm 279 mm Travel
REAR SUSPENSION	Dual A-Arm, IRS 229 mm Travel	Dual A-Arm, IRS 254 mm Travel	Dual A-Arm, IRS 254 mm Travel	Dual A-Arm, I RS 254 mm Travel	Dual A-Arm, IRS 254 mm Travel	Dual A-Arm, IRS 279 mm Travel
FRONT TYRES	25 x 9-12	25 x 8-12	25 x 8-12	25 x 10-12 / *26 x 9-12	25 x 10-12	27 x 9-12
REAR TYRES	25 x 9-12	25 x 10-12	25 x 10-12	25 x 11-12 / *26 x 11-12	25 x 11-12	27 x 11-12
WHEELS	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Aluminium Black
WHEELBASE	1830 mm	1854 mm	2020 mm / *2730 mm	2060 mm / *2870 mm	2060 mm / *2870 mm	2060 mm
DRY WEIGHT	612 kg	483 kg	486 kg / *632 kg	601 kg / *733 kg	649 kg / *766 kg	710 kg
OVERALL SIZE (L x W x H)	2790 x 1470 x 1850 mm	2790 x 1470 x 1850 mm	2900 x 1520 x 1880 mm *3700 x 1520 x 1880 mm	2960 x 1520 x 1930 mm *3750 x 1550 x 1930 mm	2960 x 1520 x 1930 mm *3750 x 1550 x 1930 mm	3050 x 1580 x 1960 mm
GROUND CLEARANCE	254 mm	254 mm	267 mm	305 mm / *287 mm	305 mm / *287 mm	330 mm
SEATING CAPACITY	2	2	3 / *6	3 / *6	3 / *6	3
FUEL CAPACITY	N/A	34 L	34 L	38 L	38 L	44 L
BED BOX DIMENSIONS	810 x 1070 x 290 mm	810 x 1070 x 290 mm	930 x 1370 x 290 mm	930 x 1370 x 290 mm	930 x 1370 x 290 mm	933 x 1378 x 3175 mm
BOX CAPACITY	227 kg	227 kg	363 kg	454 kg	454 kg	454 kg
PAYLOAD CAPACITY	454 kg	454 kg	680 kg	680 kg / *794 kg	680 kg / *794 kg	680 kg
HITCH TOWING RATING	680 kg	680 kg	680 kg	907 kg	907 kg	1134 kg
ELECTRIC POWER STEERING	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Standard
ADJUSTABLE DRIVER'S SEAT	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Standard
TILT STEERING	Standard	Standard	Standard	Standard	Standard	Standard

POLARIS SOUTH AFRICA SUPPORTS RESPONSIBLE RIDING, FOR YOUR SAFETY, ALWAYS WEAR A HELMET, EYE PROTECTION, PROTECTIVE CLOTHING AND NEVER CARRY PASSENGERS UNLESS THE ATV OR SIDE X SIDE HAS BEEN DESIGNED BY THE MANUFACTURER SPECIFICALLY FOR THAT PURPOSE. MODELS ARE FOR RIDERS AGED 16 YEARS AND OLDER. CONTACT YOUR DEALER FOR COLOUR OPTIONS. E60E

For more information and specifications visit

www.polarissa.co.za

